

MODEL	Maks. Basınç	Kapasite	Motor Gücü					Ölçüler (mm)		
	Bar	m3/dk	kW	HP	dB(A)	Ağırlık (kg)	Bağlantı Çapı	En	Boy	Yükseklik
S 18 VSD DA PRO	7.5	3.48	18.5	25	71	500	3/4 "	900	1600	1410
	10	2.92								
	13	2.37								
S 22 VSD DA PRO	7.5	4.13	22	30	71	530	3/4 "	900	1600	1410
	10	3.5								
	13	2.89								
S 30 VSD DA PRO	7.5	5.53	30	40	72	735	1 "	900	1600	1410
	10	4.77								
	13	4.03								
S 37 VSD DA PRO	7.5	7.37	37	50	73	875	1 1/4 "	1150	1500	1610
	10	6.29								
	13	5.19								
S 45 VSD DA PRO	7.5	9.31	45	60	73	955	1 1/2 "	1150	1500	1610
	10	8.02								
	13	6.64								
S 55 VSD DA PRO	7.5	11.29	55	75	74	1500	1 1/2 "	1450	1600	1750
	10	9.74								
	13	8.43								
S 75 VSD DA PRO	7.5	14.97	75	100	74	2175	2 "	1650	2000	1900
	10	12.9								
	13	10.9								
S 90 VSD DA PRO	7.5	19.03	90	125	75	2420	2 "	1650	2000	1900
	10	15.79								
	13	13.12								
S 110 VSD DA PRO	7.5	22.84	110	150	76	2800	2 "	1600	3200	1855
	10	19.27								
	13	16.06								
S 132 VSD DA PRO	7.5	26.73	132	180	78	3350	3 "	1600	3200	1855
	10	21.76								
	13	18.63								
S 160 VSD DA PRO	7.5	34.49	160	220	78	4100	3 "	1950	3500	2055
	10	28.61								
	13	23.24								
S 200 VSD DA PRO	7.5	42.68	200	270	79	5450	4 "	2150	3700	2350
	10	35.64								
	13	29.68								
S 250 VSD DA PRO	7.5	52.22	250	340	80	6400	4 "	2150	3700	2350
	10	43.82								
	13	37.3								
S 315 VSD DA PRO	7.5	62.13	315	430	81	6650	4 "	2150	3900	2350
	10	53.65								
	13	45.42								
S 355 VSD DA PRO	7.5	68.94	355	480	82	6750	4 "	2150	3900	2350
	10	60.07								
	13	51.24								