

MODEL	Maks. Basınç	Kapasite	Motor Gücü					Ölçüler (mm)		
	Bar	m3/dk	kW	HP	dB(A)	Ağırlık (kg)	Bağlantı Çapı	En	Boy	Yükseklik
S 18 VSD DA	7.5	3.27	18.5	25	71	470	3/4 "	900	1600	1410
	10	2.85								
	13	2.43								
S 22 VSD DA	7.5	3.82	22	30	71	500	3/4 "	900	1600	1410
	10	3.36								
	13	2.89								
S 30 VSD DA	7.5	5.04	30	40	71	700	1 "	900	1600	1410
	10	4.67								
	13	3.89								
S 37 VSD DA	7.5	6.42	37	50	71	840	1 1/4 "	1150	1500	1610
	10	5.58								
	13	4.77								
S 45 VSD DA	7.5	7.62	45	60	72	920	1 1/2 "	1150	1500	1610
	10	6.7								
	13	5.79								
S 55 VSD DA	7.5	10.18	55	75	74	1450	1 1/2 "	1450	1600	1750
	10	8.86								
	13	7.53								
S 75 VSD DA	7.5	13.29	75	100	75	2120	2 "	1650	2000	1900
	10	11.74								
	13	10.17								
S 90 VSD DA	7.5	16.94	90	125	75	2350	2 "	1650	2000	1900
	10	14.69								
	13	12.51								
S 110 VSD DA	7.5	20.29	110	150	76	2740	2 "	1600	3200	1855
	10	17.76								
	13	15.28								
S 132 VSD DA	7.5	23.86	132	180	77	3250	3 "	1600	3200	1855
	10	21.07								
	13	18.28								
S 160 VSD DA	7.5	30.23	160	220	77	3980	3 "	1950	3500	2055
	10	26.11								
	13	21.62								
S 200 VSD DA	7.5	41.02	200	270	78	5310	4 "	2150	3700	2350
	10	34.22								
	13	28.37								
S 250 VSD DA	7.5	50.21	250	340	78	6250	4 "	2150	3700	2350
	10	42.1								
	13	35.69								
S 315 VSD DA	7.5	55.25	315	430	79	6550	4 "	2150	3900	2350
	10	46.42								
	13	39.75								